

| | | | |
|----------------------------|-------------|-------------------------|--------|
| LOA | 40.30 | 100% Sail Area | 765 |
| LWL | 34.00 | I | 50.00 |
| Bearn | 12.10 | J | 14.70 |
| Draft | 6.50 | P | 44.20 |
| Displacement | 18,000 | E | 18.00 |
| Engine | 43 hp | SPL | 14.70 |
| Water | 77 gal | Dspl/L | 204 |
| Keel (lead) | 6,500 | SA/Dspl | 18 |
| Headroom | 6'3" | PHRF Rating | 78 |
| Height of Boat Only w/Keel | Deep 12'8" | Mast length | 55'11" |
| | Shoal 11'3" | Mast height above water | 55' |
| Running Rigging | | | |
| | Rope | Dia. | Length |
| Main halyard | Dac | 7/16" | 69'6" |
| Genoa halyard | Dac | 7/16" | 61' |
| Spin halyard | Dac | 7/16" | 111' |
| Pole lift | Dac | 3/8" | 66' |
| Flag halyard | Dac | 1/8" | 100' |
| Spreader Halyard | Dac | Cord | 50' |
| Clew reefs | Dac | 7/16" | 65' |
| Tack reefs | Dac | 7/16" | 45' |
| Main sheet | Dac | 7/16" | 82' |
| Jib sheet | Dac | 1/2" | 70' |
| Spin sheet | Dac | 7/16" | 90' |
| Afterguys | Kev/Dac | 7/16" | 90' |
| Foreguy | Dac | 3/8" | 65' |
| Traveler line | Dac | 3/8" | 22' |
| Checkstay tails | Dac | 7/16" | 80' |
| Mast & Boom | | | |
| Builder | IMI Kenyon | | |
| Mast Section | F-460 | | |
| Boom Section | 4066 | | |
| Tack Set-up | 2" | | |
| Tack Set-back | 2-1/2" | | |
| Clew Set-up | | | |
| Feeder Type | Gate | | |
| Feeder Above Boom | | | |
| Standing Rigging | | | |
| | Rod | Length | Term1 |
| Headstay | -12 | 52'3-1/2" | eye |
| Std. Backstay | -10 | 52'10" | eye |
| Intermediates | -8 | 35'10" | STMBL |
| Upper shrouds | -10 | 49'5-1/2" | STMBL |
| Lower shrouds | -12 | 20'2" | STMBL |
| Checkstay(wire) | 5/32" | 32' | Gibb T |